

PIEZO BUZZERS

PANEL MOUNTING TYPE - SCREW TERMINATION

Model No (with tin-plated tapped screw)	Operating Frequency ± 500 (Hz)	Tone	Minimum Sound Pressure at 60 cm (dB)		Operating Voltage *AC/DC Non-polar All others DC only		Operating Current (mA)		Case Style	
			At Min V	At Max V	Min V	Max V	At Min V	At Max V	Side View	Bottom View
ELB650S	2900	Continuous	70	85	4	28	4	18	A	1
ELB651S	2900	Fast Pulse	70	85	6	28	4	18	A	1
ELB653S	2900	Slow Pulse	70	85	6	28	4	18	A	1
ELB655S	2900	Continuous + Fast Pulse	70	85	6	28	4	18	A	2
ELB657S	2900	Continuous + Slow Pulse	70	85	6	28	4	18	A	2
ELB650SA	2900	Continuous	80	95	6	28	6	32	A	1
ELB651SA	2900	Fast Pulse	80	95	6	28	6	32	A	1
ELB653SA	2900	Slow Pulse	80	95	6	28	6	32	A	1
ELB655SA	2900	Continuous + Fast Pulse	80	95	6	28	6	32	A	2
ELB657SA	2900	Continuous + Slow Pulse	80	95	6	28	6	32	A	2
ELB650SAN	2900	Continuous	70	85	*4	28	4	18	A	1
ELB651SAN	2900	Fast Pulse	70	85	*6	28	4	18	A	1
ELB653SAN	2900	Slow Pulse	70	85	*6	28	4	18	A	1
ELB610SAN	2900	Continuous	70	85	*30	120	4	18	A	1
ELB611SAN	2900	Fast Pulse	70	85	*30	120	4	18	A	1
ELB613SAN	2900	Slow Pulse	70	85	*30	120	4	18	A	1
ELB620SAN	2800	Continuous	70	85	*60	250	4	18	B	1
ELB621SAN	2900	Fast Pulse	70	85	*60	250	4	18	B	1
ELB623SAN	2900	Slow Pulse	70	85	*60	250	4	18	B	1
ELB648S	2900	Continuous	70	85	10	48	4	18	A	1
ELB750S	3600	Continuous	70	85	4	28	4	18	E	4
ELB751S	3600	Fast Pulse	70	85	6	28	4	18	E	4
ELB753S	3600	Slow Pulse	70	85	6	28	4	18	E	4
ELB755S	3600	Continuous + Fast Pulse	70	85	6	28	4	18	E	5
ELB757S	3600	Continuous + Slow Pulse	70	85	6	28	4	18	E	5
ELB660S	1500-4000	Siren	95	105	6	15	100	200	B	1
ELB680S	2900	Hi-Low	95	105	6	15	100	200	B	1

ELB650S series fit 1.125 inch (28.57 mm) diameter opening in panels to 0.125 inch (3.17 mm) thick.
 ELB750S series fit 1.25 inch (31.75 mm) diameter opening in panels to 0.50 inch (12.54 mm) thick.
 Pulse Rate at 12 VDC: 3.0 ± 20% Hz (Fast pulse) 1.2 ± 20% Hz (Slow pulse)

For case style see next page