

1 Digit Numeric Displays

0.39" ~ 0.40"

IF=20mA/segment Ta=25°C

Front View	Device No		Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)	
	Common Anode	Common Cathode	Emitter	Surface, Segment	λ_p	λ_d		Minimum	Typical
0.39" 10pin fig 13-5	HDA-3912	HDC-3912	hi-red	GW,BW,BR,RR	700	658	2.1	300	550
	HDA-3913	HDC-3913	yellow green	GW,BW,GGn	565	564	2.1	700	1600
	HDA-3914	HDC-3914	yellow	GW,BW,GY,BY	585	583	2.1	600	1500
	HDA-3915	HDC-3915	hi-eff red	GW,BW,BR,RR	635	620	2.0	700	1800
	HDA-3916DR	HDC-3916DR	super red	GW,BW,BR,RR	660	645	1.8	1600	8000
0.39" 10pin fig -6	HDA-3912-A	HDC-3912-A	hi-red	GW,BW,BR,RR	700	658	2.1	300	550
	HDA-3913-A	HDC-3913-A	yellow green	GW,BW,GGn	565	564	2.1	700	1600
	HDA-3914-A	HDC-3914-A	yellow	GW,BW,GY,BY	585	583	2.1	600	1500
	HDA-3915-A	HDC-3915-A	hi-eff red	GW,BW,BR,RR	635	620	2.0	700	1800
	HDA-3916DR-A	HDC-3916DR-A	super red	GW,BW,BR,RR	660	645	1.8	1600	8000
0.40" 14pin fig -7	HDA-4012	HDC-4012	hi-red	GW,BW,BR,RR	700	658	2.1	300	650
	HDA-4013	HDC-4013	yellow green	GW,BW,GGn	565	564	2.1	800	2000
	HDA-4014	HDC-4014	yellow	GW,BW,GY,BY	585	583	2.1	700	1600
	HDA-4015	HDC-4015	hi-eff red	GW,BW,BR,RR	635	620	2.0	800	2000
	HDA-4016DR	HDC-4016DR	super red	GW,BW,BR,RR	660	645	1.8	1600	5000
0.40" 10pin fig -8	HDA-4012-A	HDC-4012-A	hi-red	GW,BW,BR,RR	700	658	2.1	300	550
	HDA-4013-A	HDC-4013-A	yellow green	GW,BW,GGn	565	564	2.1	700	1600
	HDA-4014-A	HDC-4014-A	yellow	GW,BW,GY,BY	585	583	2.1	600	1500
	HDA-4015-A	HDC-4015-A	hi-eff red	GW,BW,BR,RR	635	620	2.0	700	1800
	HDA-4016DR-A	HDC-4016DR-A	super red	GW,BW,BR,RR	660	645	1.8	1500	5000

Dimension:

Unit : mm. Tolerance:0.25mm.

