

2 Digit Numeric Displays

0.30" ~ 0.40"

IF=20mA/segment Ta=25°C

Front View	Device No		Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)	
	Common Anode	Common Cathode	Emitter	Surface, Segment	λ_p	λ_d		Minimum	Typical
0.30" $\frac{E}{10}$ 10pin fig 6-25	HDA-3022	HDC-3022	hi-red	GW,BW,BR,RR	700	658	2.1	300	550
	HDA-3023	HDC-3023	yellow green	GW,BW,GGn,BGn	565	564	2.1	700	1600
	HDA-3024	HDC-3024	yellow	GW,BW,GY,BY	585	583	2.1	600	1500
	HDA-3025	HDC-3025	hi-eff red	GW,BW,BR,RR	635	620	2.0	700	1800
	HDA-3026DR	HDC-3026DR	super red	GW,BW,BR,RR	660	645	1.8	1500	5000
0.30" $\frac{E}{16}$ 16pin fig 6-26	HDA-3022-16	HDC-3022-16	hi-red	GW,BW,BR,RR	700	658	2.1	300	550
	HDA-3023-16	HDC-3023-16	yellow green	GW,BW,GGn	565	564	2.1	700	1600
	HDA-3024-16	HDC-3024-16	yellow	GW,BW,GY,BY	585	583	2.1	600	1500
	HDA-3025-16	HDC-3025-16	hi-eff red	GW,BW,BR,RR	635	620	2.0	700	1800
	HDA-3026DR-16	HDC-3026DR-16	super red	GW,BW,BR,RR	660	645	1.8	1500	5000
0.36" $\frac{E}{10}$ 10pin fig 6-27	HDA-3622	HDC-3622	hi-red	GW,BW,BR,RR	700	658	2.1	300	550
	HDA-3623	HDC-3623	yellow green	GW,BW,GGn,BGn	565	564	2.1	700	1600
	HDA-3624	HDC-3624	yellow	GW,BW,GY,BY	585	583	2.1	600	1500
	HDA-3625	HDC-3625	hi-eff red	GW,BW,BR,RR	635	620	2.0	700	1800
	HDA-3626DR	HDC-3626DR	super red	GW,BW,BR,RR	660	645	1.8	1500	5000
0.40" $\frac{E}{16}$ 16pin fig 6-28	HDA-4022	HDC-4022	hi-red	GW,BW,BR,RR	700	658	2.1	300	6500
	HDA-4023	HDC-4023	yellow green	GW,BW,GGn	565	564	2.1	800	2000
	HDA-4024	HDC-4024	yellow	GW,BW,GY,BY	585	583	2.1	700	1600
	HDA-4025	HDC-4025	hi-eff red	GW,BW,BR,RR	635	620	2.0	800	2000
	HDA-4026CR	HDC-4026CR	super red	GW,BW,BR,RR	660	645	1.8	2000	10000

Dimension:

Unit : mm. Tolerance:0.25mm.

