

2 Digit Numeric Displays

0.50" ~ 0.80"

IF=20mA/segment Ta=25°C

Front View	Device No		Color		Wavelength (nm)		VF Typical (V)	Brightness (mcd)	
	Common Anode	Common Cathode	Emitter	Surface, Segment	λ_p	λ_d		Minimum	Typical
0.50" $\frac{E}{E}$ 10pin fig 6-33	HDA-5022-10	HDC-5022-10	hi-red	GW,BW,BR,RR	700	658	2.1	300	650
	HDA-5023-10	HDC-5023-10	yellow green	GW,BW,GGn	565	564	2.1	750	2000
	HDA-5024-10	HDC-5024-10	yellow	GW,BW,GY,BY	585	583	2.1	700	1600
	HDA-5025-10	HDC-5025-10	hi-eff red	GW,BW,BR,RR	635	620	2.0	750	2000
	HDA-5026DR-10	HDC-5026DR-10	super red	GW,BW,BR,RR	660	645	1.8	2000	6000
	HDA-5026CR-10	HDC-5026CR-10	super red	GW,BW,BR,RR	660	645	1.8	5600	21000
0.52" $\frac{E}{E}$ 18pin fig 6-34	HDA-5222	HDC-5222	hi-red	GW,BW,BR,RR	700	658	2.1	300	650
	HDA-5223	HDC-5223	yellow green	GW,BW,GGn	565	564	2.1	750	2000
	HDA-5224	HDC-5224	yellow	GW,BW,GY,BY	585	583	2.1	700	1600
	HDA-5225	HDC-5225	hi-eff red	GW,BW,BR,RR	635	620	2.0	750	2000
	HDA-5226DR	HDC-5226DR	super red	GW,BW,BR,RR	660	645	1.8	2000	6000
	HDA-5226CR	HDC-5226CR	super red	GW,BW,BR,RR	660	645	1.8	5600	21000
0.56" $\frac{E}{E}$ 18pin fig 6-35	HDA-5622	HDC-5622	hi-red	GW,BW,BR,RR	700	658	2.1	300	650
	HDA-5623	HDC-5623	yellow green	GW,BW,GGn	565	564	2.1	750	2000
	HDA-5624	HDC-5624	yellow	GW,BW,GY,BY	585	583	2.1	700	1600
	HDA-5625	HDC-5625	hi-eff red	GW,BW,BR,RR	635	620	2.0	750	2000
	HDA-5626DR	HDC-5626DR	super red	GW,BW,BR,RR	660	645	1.8	2000	6000
	HDA-5626CR	HDC-5626CR	super red	GW,BW,BR,RR	660	645	1.8	5600	21000
0.80" $\frac{E}{E}$ 18pin fig 6-36	HDA-8022	HDC-8022	hi-red	GW,BW,BR,RR	700	658	2.1	400	700
	HDA-8023	HDC-8023	yellow green	GW,BW,GGn	565	564	2.1	750	3000
	HDA-8024	HDC-8024	yellow	GW,BW,GY,BY	585	583	2.1	750	3000
	HDA-8025	HDC-8025	hi-eff red	GW,BW,BR,RR	635	620	2.0	750	3000
	HDA-8026DR	HDC-8026DR	super red	GW,BW,BR,RR	660	645	1.8	2000	7000
	HDA-8026CR	HDC-8026CR	super red	GW,BW,BR,RR	660	645	1.8	6000	21000

Dimension:

Unit : mm. Tolerance:0.25mm.

