

3 Digit Numeric Displays

0.30" ~ 0.40"

IF=20mA/segment Ta=25°C

Front View	Device No		Color		Wavelength (nm)		VF Typical (V)	Brightness (μcd)	
	Common Anode	Common Cathode	Emitter	Surface, Segment	λ p	λ d		Minimum	Typical
0.30" $\frac{E}{12}$ pin fig 6-41	HDA-3032	HDC-3032	hi-red	GW,BW,BR,RR	700	658	2.1	300	550
	HDA-3033	HDC-3033	yellow green	GW,BW,GGn,BGn	565	564	2.1	700	1600
	HDA-3034	HDC-3034	yellow	GW,BW,GY,BY	585	583	2.1	600	1500
	HDA-3035	HDC-3035	hi-eff red	GW,BW,BR,RR	635	620	2.0	700	1800
	HDA-3036DR	HDC-3036DR	super red	GW,BW,BR,RR	660	645	1.8	1500	6000
0.36" $\frac{E}{16}$ pin fig 6-42	HDA-3632	HDC-3632	hi-red	GW,BW,BR,RR	700	658	2.1	300	550
	HDA-3633	HDC-3633	yellow green	GW,BW,GGn,BGn	565	564	2.1	700	1600
	HDA-3634	HDC-3634	yellow	GW,BW,GY,BY	585	583	2.1	600	1500
	HDA-3635	HDC-3635	hi-eff red	GW,BW,BR,RR	635	620	2.0	700	1800
	HDA-3636DR	HDC-3636DR	super red	GW,BW,BR,RR	660	645	1.8	1700	8000
0.40" $\frac{E}{24}$ pin fig 6-43	HDA-4032	HDC-4032	hi-red	GW,BW,BR,RR	700	658	2.1	300	650
	HDA-4033	HDC-4033	yellow green	GW,BW,GGn	565	564	2.1	800	2000
	HDA-4034	HDC-4034	yellow	GW,BW,GY,BY	585	583	2.1	700	1600
	HDA-4035	HDC-4035	hi-eff red	GW,BW,BR,RR	635	620	2.0	800	2000
	HDA-4036DR	HDC-4036DR	super red	GW,BW,BR,RR	660	645	1.8	1600	5000
0.40" $\frac{E}{12}$ pin fig 6-44	HDA-4032-12	HDC-4032-12	hi-red	GW,BW,BR,RR	700	658	2.1	300	650
	HDA-4033-12	HDC-4033-12	yellow green	GW,BW,GGn	565	564	2.1	800	2000
	HDA-4034-12	HDC-4034-12	yellow	GW,BW,GY,BY	585	583	2.1	700	1600
	HDA-4035-12	HDC-4035-12	hi-eff red	GW,BW,BR,RR	635	620	2.0	800	2000
	HDA-4036DR-12	HDC-4036DR-12	super red	GW,BW,BR,RR	660	645	1.8	1600	5000
HDA-4036CR-12	HDC-4036CR-12	super red	GW,BW,BR,RR	660	645	1.8	5000	20000	

Dimension:

Unit : mm.Tolerance:0.25mm.

