

SPECIFICATION :

MECHANICAL :

1. **Housing Material** : ABS & PC mixed. UL 94V-0 rated.

Insert Material : PBT UL 94V-0 rated.

Contact Finished : 50 micro-inch gold over.

nickel 50-60 micro-inch.

2. **IDC Housing** : PC UL 94V-0.


IDC Terminal : Phosphor Bronze. nickel plated 50-60 micro-inch.

3. **Housing Color** : OPTIONAL.

(Black, Blue, Gray, Green, Ivory, Orange, Red, White, Yellow)

4. **P.C.B** : FR4 1.2 m/m thickness, 2 layer.

5. **I.D.C CAP** : ABS UL-HB white color.



STICKER

T568B

PIN.5 WHITE/BLUE
PIN.4 BLUE
PIN.1 WHITE/ORANGE
PIN.2 ORANGE
PIN.3 WHITE/GREEN
PIN.6 GREEN
PIN.7 WHITE/BROWN
PIN.8 BROWN

T568A

PIN.5 WHITE/BLUE
PIN.4 BLUE
PIN.1 WHITE/GREEN
PIN.2 GREEN
PIN.3 WHITE/ORANGE
PIN.6 ORANGE
PIN.7 WHITE/BROWN
PIN.8 BROWN