

SPECIFICATION :

MECHANICAL :

1. *Housing Material : ABS & PC mixed. UL 94V-0 rated.*

Insert Material : PBT UL 94V-0 rated.

Contact Finished : 50 micro-inch gold over.

nickel 50-60 micro-inch.

2. *IDC Housing : PC UL 94V-0.*



IDC Terminal : Phosphor Bronze, nickel plated 50-60 micro-inch.

3. *Housing Color : OPTIONAL.*

(Black, Blue, Gray, Green, Ivory, Orange, Red, White, Yellow)

4. *P.C.B : FR4 1.2 m/m thickness, 2 layer.*

5. *I.D.C CAP : ABS UL-HB white color.*



STICKER

T568B

PIN.5 WHITE/BLUE
PIN.4 BLUE
PIN.1 WHITE/ORANGE
PIN.2 ORANGE
PIN.3 WHITE/GREEN
PIN.6 GREEN
PIN.7 WHITE/BROWN
PIN.8 BROWN

T568A

PIN.5 WHITE/BLUE
PIN.4 BLUE
PIN.1 WHITE/GREEN
PIN.2 GREEN
PIN.3 WHITE/ORANGE
PIN.6 ORANGE
PIN.7 WHITE/BROWN
PIN.8 BROWN